

Open Frame LCD

Open Frame LCD



17"

Specifications


RoHS
COMPLIANT
2002/95/EC

Model Name	S17L500-OFM1
Viewable Size Image	17"
Active Display Area(mm)	337.92(H)x270.34(V)
Pixel Pitch(mm)	0.264(H)x0.264(V)
Number of Pixels	1280x1024
Contrast Ratio	1000:1(typ.)
Display Color	16.7M
Brightness(cd/m ²)	350(typ.)
Viewing Angle(CR>=10)	-85~85(H);-80~80(V)
Synchronization Range	
Horizontal/Vertical	31.5~80.0KHz/60~75Hz
Recommended Resolution	1280 x1024@60Hz, 75Hz
Signal Connector	15 pin D-Sub
Power Source	12 V DC in, with External AC to DC Adapter (100~240V AC)
Power Consumption	36 W typical, normal operation
Power Management	VESA DPMS Compliant
Plug & Play	VESA DDC 1/2B
Optional Video Input	S-Video, Composite
Optional DVI Input	Yes
Optional Touch Screen	Resistive, Capacitive, SAW

Remarks:S17L500 series= VGA input only

S17L540 series= VGA+Video Input

Mechanical Drawing



* Note: this is a simplified drawing and some components are not marked in detail. Please contact our sales representative if you need further product information.

Rev.	Reasons	Revised Date
1.5	Spec Change	Apr-24-13
1.6	Change pic	June-13-13
1.7	Spec Change	Nov-06-13