

Model Name : M700D

Product Features:

- Intel® Atom™ Processor Dual Core N2600 1.6 GHz
- 7"WSVGA(1024x600)TFT LCD Display
- Compliant with MIL-STD-810G
- Projected Capacitive Multi-Touch Screen
- 2.0M Camera in Rear Side (with LED auxiliary light, Auto Focus)
- G-sensor and Light sensor
- Built-in WLAN 802.11 a/b/g/n & Bluetooth 4.0 + Class I
- Neo-6 GPS
- Windows Embedded 8 Standard




Product Specifications:

System Specification	Processor	Intel® Atom™ Processor N2600 1.6 GHz
	System Memory	2 GB DDR3 SDRAM(upgradable to 4 GB)
	Storage	32GB SSD(upgradable to 128 GB SSD)
	Operating System	Windows Embedded 8 Standard
Display Specification	Size	7"
	Resolution	1024 * 600
	Brightness	500nit (typ.)
	Touch	Projected Capacitive Touch
Wireless Communication	WLAN	Support 802.11 a/b/g/n 2T2R
	Bluetooth	Bluetooth 4.0 + Class I
	WWAN	Optional 3G(support HSPA/ UMTS / GPRS / WCDMA / GSM)
	GPS	Built-in Neo-6 GPS module
Mechanical and Environment	Dimensions (W x L x H)	212.4 x 132.8 x 25 mm (Standard)
	Weight	770g (Standard) / 1070g (with second battery)
	Operation Temperature	-20°C to 60°C (AC mode), -10°C to 50°C (Battery mode)
	Operation Humidity	95% RH (non condensing)
	IP Proof	IP65
	Shock	MIL-STD-810G Method 516.5
	Vibration	MIL-STD-810G Method 514.5
	Drop	MIL-STD-810G Method 516.5, 4 ft, Free to concrete
I/O Connectors	External I/O	1 x USB 2.0 A Type 1 x Headset jack 1 x 2.5Ø 12V DC Power Input 1 x SIM Slot 1 x Micro SD Card 1 x Docking Port (For charge and USB)
	Internal Audio Device	1.2W Speaker
	Optional Battery	1 x Second battery
Power Management	Power input	12V DC in
	Power consumption	11.5W (under full loading)
	Battery	7.4V 2270mAh Li-Poly rechargeable battery 2S1P 7.4V 5200mAh Hotswap second battery 2S1P
	Battery Operating Time	Main Battery: 3hrs* With Second Battery: 10hrs*
Adapter	50W Adapter	
Field Service Features	Camera	2.0M pixel Camera with LED auxiliary light(Rear Side , with Auto Focus)

* Note: Measured at dimming LCD brightness. Varies depending on the usage conditions, or when an external device is attached.

Dimensions :



Accessories:	
Default	Quick Start Guide
	User Manual
	50W Adapter
	5200mAh Second battery

Order Information:	
Model Name	Configuration
M700D	Standard
M700D-3	with 3G card