


7" Compact Rugged tablet PC

Model :W07I98M-RTA4R

Feature:

- 7" 800 x 480 Resolution LED Sunlight Readable Panel
- Fanless Low-power system with Intel® Atom Z510 processor.
- Support SODIMM DDR2 memory (Max. up to 2GB)
- Built-in Wi-Fi/ Bluetooth/and GPS Module
- Support 3G function (for optional)
- 1 x Lithium-ion Standard Battery/2600 mAh
- MIL-STD-810G compliance with high, low temperature, humidity, and altitude, Shock, Vibration, and transit drop.



Note: this is a simplified drawing and some components are not marked in detail. Please contact our sales representative if you need further product information.

System Specification

Processor	: Intel® Atom Z510 1.1GHz
System Chipset	: Intel® US15W Chipset
System Memory	: 1GB SODIMM DDR2 (Max. up to 2GB)
Storage	: 8GB mPATA SSD (Max up to 128GB)
Audio	: 0.8W speaker (Internal)
• Intel Atom Z530 1.6GHz CPU is optional by request	

Control buttons

Control Button	: Power button 1 x MENU Key control Brightness, Volume and Battery Status. 1 x Up key, 1 x Down key, 1 x Left key, 1 x Right key.
LED indicator	: 3 programmable Hotkeys/ Max. 6 Functions Power on/off / Battery/ HDD Access

Mechanical and Environment

Dimensions (W x L x H)	: 126.6(W) x 235(L) x 42(H)
Weight	: 1.1Kg(estimated)
Operation Temperature	: -20°C to 60°C (AC mode), -10°C to 50°C (Battery mode)
Battery charging Temp.	: 0° C ~ 35° C
Operation Humidity	: 30%~90% (non condensing)
IP Proof	: IP65
Shock	: MIL-STD-810G M516.5
Vibration	: MIL-STD-810G M514.5
Drop	: MIL-STD-810G M516.5, 4 ft, Free to concrete
Certifications	: CE, FCC Class B

I/O Connectors

I/O Port	: 1 x Power connector, 1 x LAN, 1 x USB, 1 x Line out, 1 x Mic in
----------	---

Power Management

Power input	: 12V DC
Battery	: Lithium ion 2600mAh battery
Battery Operating Time	: 3 Hours *
Adapter	: 100- 240 V , 50-60 Hz / 12V DC input

Display Specification

Pixel Number	: 800(H) x 480(V)
Brightness	: 400 cd/m2 (typical)
Touch (Default)	: 4-Wire Resistive touch

Docking Cable Spec

I/O (default)	: 1 x docking connector support 1x USB, 1 x COM
I/O (optional)	: 1 x docking connector support 2 x USB 1 x COM , 1 X VGA

**Note: Measured at dimming LCD brightness. Varies depending on the usage conditions, or when an external device is attached..

Note: All Specifications are subject to change without prior notice!